

SCHOOLSAFE® STANDARD



SCHOOLSAFE® STANDARD



VARIOUS INTERLAYERS
GLASS, POLYCARBONATE &
POLYURETHANE

WEIGHT
4.5LB/SQ.FT.

FORCED ENTRY RESISTANT GLASS FOR SCHOOL AND EDUCATIONAL SETTINGS

SPECIFICATIONS

*ASTM F3561

STANDARD TEST
METHOD FOR FORCED-
ENTRY-RESISTANCE OF
FENESTRATION SYSTEMS
AFTER SIMULATED ACTIVE
SHOOTER ATTACK.

MEETS OR EXCEEDS F3561 (NEW BENCHMARK ADOPTED IN 2022)

THIS PRODUCT MET OR EXCEEDED THE TEST* THAT FEATURED
THE FOLLOWING PROCEDURE:

A TEST CONSISTING OF WEAKENING OF THE FENESTRATION
SYSTEM USING BALLISTIC PROJECTILES (5.56 NATO, M193, 55
GRAIN FMJ) WHICH IS FOLLOWED BY MECHANICALLY DRIVEN
IMPACTS USING A FORCED ENTRY IMPACTOR CAPABLE OF
DELIVERING HORIZONTAL IMPACTS OF 400FT-LBF TO SIMULATE
THE ACTIVE SHOOTER EVENT.

END RESULT: THE PRODUCT ACHIEVES A LEVEL OF 1-8 FOR
FORCED ENTRY RESISTANCE.

TECHNICAL DATA

- NOMINAL THICKNESS: 3/8"
- WEIGHT PER SQUARE FOOT: 4.5LB

GLAZING OPTIONS

- CLEAR
- LOW IRON

*CONTACT US FOR ADDITIONAL
GLASS TYPES & GLAZING OPTIONS*

FRAMING OPTIONS

- ALUMINUM STORE FRONT
- ALUMINUM CURTAIN WALL

SIZING INFORMATION

- UP TO 60" X 96"

